

TEST REPORT

No. : GZMR090404100

Date : Apr 03, 2009

Page: 1 of 2

HUIDONG MEIXIN PLASTIC LUMBER PRODUCTS MANUFACTURING CO., LTD
NGA INDUSTRIAL PARK, DALING, HUIDONG, GUANGDONG PROVINCE, PRC


The following sample(s) was/ were submitted and identified on behalf of the client as:

Sample Name : NEWTECHWOOD
Sample Information : 090113-1
SGS Ref No. : GP090400526-8.8
Test Performed : Selected test(s) as requested by applicant
Date of Receipt : Apr 02, 2009
Test Period : Apr 02, 2009 to Apr 03, 2009

Test result(s) : Please refer to the following page(s)

*****To be continued*****

Signed for and on behalf of
SGS-CSTC Ltd.



Cathy Peng
Technical Supervisor

This document is issued by the Company under its General Conditions of Service printed overleaf or available on request and accessible at <http://www.sgs.com/terms.and.conditions.htm>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the technical findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. This document cannot be reproduced except in full without prior approval of the Company.

GZMR 014812



TEST REPORT

No. : GZMR090404100

Date : Apr 03, 2009

Page: 2 of 2

Test Result(s):

Sample description: Grey bar

Test item: Flexural modulus

Test method: ASTM D790--07^{ed} method A

Specimen: 128×12.37×3.42mm

Testing speed: 1.5mm/min

Span: 55mm

Flexural modulus: 3070MPa

Note: This report is the English version of No.GZMR090303173.

*****End of report*****

This document is issued by the Company under its General Conditions of Service printed overleaf or available on request and accessible at http://www.sgs.com/terms_and_conditions.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. This document cannot be reproduced except in full without prior approval of the Company.